

VALIANT

Dead Flat Lacquer V-620



DESCRIPTION:

A premium quality lacquer varnish topcoat that dries to an extremely durable flat finish.

RECOMMENDED USES:

Interior wood surfaces.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOSITY	: 65-70 kus
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 5 minutes
DRY HARD	: 1 hour
COATING INTERVAL	: 1 hour
THINNING	: Reduce with Lacquer Thinner
APPLICATION	: spray
COVERAGE	: 30-35 m ² /4L
CLEAN-UP	: Lacquer Thinner
PACKAGING SIZE	: 1, 4, 16 liters
AVAILABLE COLORS	:

SURFACE PREPARATION:

New or unpainted surface

Use kiln-dried wood with a maximum moisture content of 12%. Sand wood until smooth. Counter sink nail heads then putty. Dust the surface and wipe clean.

Old or previously painted or stained surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil, and other contaminants by scraping. Sand the surface. Dust the surface and wipe clean.

APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

PAINTING DIRECTIONS: For best results use:

- 1st coat: Valiant Chemotite Wood Putty V-660. Allow 30 minutes drying time then scuff sand using 300 grit or finer.
- 2nd coat: Valiant Sanding Sealer V-610. Allow 1 hour drying time then scuff sand using 400 grit or finer.
- 3rd – 4th coat: Valiant Clear Gloss Lacquer V-600 or Valiant Dead Flat Lacquer V-620. Allow 1 hour drying time between coats.