

VALIANT

Chemotite Lacquer Putty V-660



DESCRIPTION:

A lacquer-type putty/filler for repairing surface imperfections such as cracks and holes in wood.

This product is fast drying and has easy sanding properties with a neutral color for convenient tinting.

RECOMMENDED USES:

All interior wood surfaces.

PRODUCT APPEARANCE	: Yellow Paste
PACKAGE VISCOSITY	: Heavy paste
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 30 minutes
DRY HARD	: 1 hour
COATING INTERVAL	: 1 hour
THINNING	: Apply at package consistency
APPLICATION	: Putty knife
COVERAGE	: 8-10 m ² /4L depending on surface porosity & texture
CLEAN-UP	: Lacquer Thinner
PACKAGING SIZE	: 1, 4 liters
AVAILABLE COLORS	: Natural V-660

SURFACE PREPARATION:

New or unpainted surface

Use kiln-dried wood with a maximum moisture content of 12%. Sand wood until smooth. Counter sink nail heads then putty. Dust the surface and wipe clean.

Old or previously painted or stained surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil, and other contaminants by scraping. Sand the surface. Dust the surface and wipe clean.

APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

PAINTING DIRECTIONS: For best results use:

- 1st coat: Valiant Chemotite Wood Putty V-660. Allow 30 minutes to dry.
Scuff sand using 300 grit or finer.
- 2nd coat: Valiant Sanding Sealer V-610. Allow 1 hour drying time.
Scuff sand using 400 grit or finer.
- 3rd – 4th coat: Valiant Clear Gloss Lacquer V-600 or Valiant Dead Flat Lacquer V-620.
Allow 1 hour drying time between coats.