

UNIVERSAL PROFESSIONAL

Surface Preparation Concrete Putty



DESCRIPTION:

A premium quality water-based surface preparation product for patching and filling minor surface unevenness. This high quality putty is formulated to resist shrinking and cracking. This product can also be use as a full putty system.

RECOMMENDED USES:

Interior concrete, stucco, bricks and plaster.

PRODUCT APPEARANCE	: Liquid
PACKAGE VISCOSITY	: Thick paste
DRY FILM THICKNESS	:
DRY SET TO TOUCH	: 30 minutes
DRY HARD	: 4 hours
COATING INTERVAL	: 1-2 hours depending on temperature
THINNING	: Do not reduce
APPLICATION	: putty knife
COVERAGE	: 8-10 m ² /4L depending on thickness & texture
CLEAN-UP	: Water
PACKAGING SIZE	: 1, 4, 16 liters
AVAILABLE COLORS	: White PRO-10
FINISH	: Flat

SURFACE PREPARATION:

New or unpainted surface

Remove dirt, dust, grit, loose mortar, oil, grease and other contaminants. New concrete must be cured at least 28 days before paint application. Please follow manufacturer's recommendation to check use litmus paper test.

Old or previously painted surface

Remove all loose, peeling, chalking or blistering paint, dirt, dust, grease, oil and other contaminants. Treat mold or fungus infestation with bleaching solution (1 part bleach and 3 parts water).

APPLICATION:

Do not thin. Inter-mix all cans of same color to ensure color uniformity and consistency. Always stir paint before and occasionally during application. Apply only when temperature is from 10° – 35°C. Do not paint in rain or rain imminent weather. For best results always use high quality roller and brush.

UNIVERSAL PROFESSIONAL

Surface Preparation Concrete Putty



PAINTING DIRECTIONS: For best results use:

- 1st coat: Universal Professional Flat Latex White PRO-100 or
Universal Base Coat Acrylic Primer PRO-50. Allow 1 hour drying time.
- 2nd coat: Universal Professional Concrete Putty White PRO-10
Spot or full putty. Allow 4 hours drying time.
Spot prime or full prime with Universal Professional Flat Latex White
PRO-100 or Universal Base Coat Acrylic Primer PRO-50.
Allow 1 hour drying time.
- 3rd – 4th coat: Universal Professional Latex of desired sheen & color.